

**VILLAGE OF WINDSOR
ORDINANCE 2020-10**

**AN ORDINANCE AMENDING CHAPTER 42 OF THE CODE OF ORDINANCES
REGARDING DRIVEWAY CONSTRUCTION STANDARDS**

WHEREAS, the Village Staff recommends certain amendments be made to the Village of Windsor Code of Ordinances regarding driveway construction standards; and

WHEREAS, the Village Board finds it to be in the public interest to amend Chapter 42 concerning driveway construction standards.

NOW, THEREFORE, the Village Board of the Village of Windsor, Dane County, Wisconsin do ordain as follows:


SECTION 1. Chapter 42, Article II, Section 42-60 of the Windsor Code of Ordinances is hereby amended as set forth in Exhibit A attached hereto.

SECTION 2. All other provisions of Code of Ordinances not specifically amended herein shall remain unmodified and in full force and effect.

SECTION 3. This ordinance shall take effect upon passage and publication as provided by law.

The above and foregoing Ordinance was duly adopted at a meeting of the Village Board of the Village of Windsor held on September 17th, 2020, by a vote of 5 in favor and 0 opposed.

VILLAGE OF WINDSOR


Robert E. Wipperfurth, Village President

Attested by:


Christine Capstran, Village Clerk

Published: 9-24-20

Effective: 9-25-20

Exhibit A

Sec. 42-60. - Driveway construction standards.

~~(a) *Width.* That portion of the driveway that is constructed within the right-of-way shall not be less than 18 feet in width. Driveways for all types of land uses shall not be wider than 30 feet. Exceptions may be granted by the Village Board based on factors such as accommodating commercial or farm vehicles, where left and right turn lanes should be included within the driveway, or other reasons deemed appropriate for public health and safety.~~

(a) *Width.*

1. Minimum Width – All constructed driveways shall not be less than 18 feet in width within the right-of-way.
 2. Maximum Width (Residential & Non-Residential) – Residential and non-residential driveways shall not be greater than 30 feet in width within the right-of-way.
 3. Maximum Width (Agricultural) – Agricultural driveways shall not be greater than 45 feet within the right-of-way.
 4. A special exception to the maximum width of a driveway may be granted by the Director of Public Works (or designee) based on factors such as accommodating the turning radii of large-scale vehicles, trailers and equipment, or other reasons deemed appropriate for public health and safety. At the discretion of the Director of Public Works (or designee), the special exception to the maximum width of a driveway may require discussion and action by the Public Works Committee and Village Board.
- (b) *Angle of approach.* Horizontally, the angle between the center line of the driveway and the centerline of the road shall not be less than 70 degrees. Vertically, the angle of the driveway surface shall not exceed a slope of ten percent.
- (c) *Surface other than as described in article IV of chapter 38.* Driveways may be constructed of concrete, asphalt, or any other material approved by the Director of Public Works, and shall be placed so that the surface of the driveway meets the existing edge of pavement. On roads without curb and gutter, there shall be a four-foot asphalt transition area between the asphalt public roads and concrete driveways, or there shall be a concrete expansion joint installed four-foot from the edge of pavement of asphalt public roads.
- (d) *Obstruction of roadway prohibited.* Driveways shall not extend into the roadway surface so as to cause an obstruction to the maintenance or snow removal on the roadway.